

Product Code	P/LT	Size	XL	L.I	S.S	Ply	Max Air (psi)	Max Load (lbs)		Rim	
								S	D	Measuring	Approved
15717		225/45R15		87	W	4	51	1,201	-	7.5	7.0~8.5
15718		205/55R16		91	W	4	51	1,356	-	6.5	5.5~7.5
15719		225/50R16		92	W	4	51	1,389	-	7.0	6.0~8.0
15720		215/45R17		87	Y	4	51	1,201	-	7.0	7.0~8.0
15721		225/45R17		91	Y	4	51	1,356	-	7.5	7.0~8.5
15722		235/45R17		94	Y	4	51	1,447	-	8.0	7.5~9.0
15723		245/40R17		91	Y	4	51	1,356	-	8.5	8.0~9.5
15724		255/40R17		94	Y	4	51	1,447	-	9.0	8.5~10.0
15725		225/40R18		88	Y	4	51	1,235	-	8.0	7.5~9.0
15726		225/45R18		91	Y	4	51	1,356	-	7.5	7.0~8.5
15727		235/40R18		91	Y	4	51	1,356	-	8.5	8.0~9.5
15728		245/40R18		93	Y	4	51	1,433	-	8.5	8.0~9.5
15729		255/35R18		90	Y	4	51	1,323	-	9.0	8.5~10.0
15736		265/35R18		93	Y	4	51	1,433	-	9.5	9.0~10.5
15621		275/40R18		99	Y	4	51	1,709	-	9.5	9.0~11.0
15730		275/35R18		95	Y	4	51	1,521	-	9.5	9.0~11.0
15731		225/40R19		89	Y	4	51	1,279	-	8.0	7.5~9.0
15732		235/35R19		87	Y	4	51	1,201	-	8.5	8.0~9.5
15733		245/40R19		94	Y	4	51	1,477	-	8.5	8.0~9.5
15734		275/35R19		96	Y	4	51	1,565	-	9.5	9.0~11.0
16674		275/40R20		102	W	4	51	1,874	-	9.5	9.0~11.0
17387		275/40R20		102	Y	4	51	1,874	-	9.5	9.0~11.0

. Technical Data can be changed without further notice.

. For more detail OE application information, please refer to "Original Equipment 2020" page.

\* Symmetric Tread Design

. 16674 (275/40R20W) - while the supply lasts

Section	Overall Width (inch)	Tread Diameter (inch)	Tread Depth (/32")	U.T.Q.G			Sidewall	MSRP	OE
				Treadwear	Traction	Temp.			
8.9	23.0	9.0	200	A	A	Black	130.98		
8.4	24.9	7.5	200	A	A	Black	125.98		
9.2	24.9	9.0	200	A	A	Black	133.98		
8.4	24.6	7.5	200	A	A	Black	138.98		
8.9	25.0	7.5	200	A	A	Black	144.98		
9.3	25.4	9.0	200	A	A	Black	155.98		
9.8	24.7	9.0	200	A	A	Black	165.98		
10.2	25.0	9.0	200	A	A	Black	169.98		
9.1	25.1	9.0	200	A	A	Black	185.98		
8.9	25.9	9.0	200	A	A	Black	185.98		
9.5	25.4	7.5	200	A	A	Black	204.98		
9.8	25.7	7.5	200	A	A	Black	213.98		
10.2	25.0	9.0	200	A	A	Black	250.98		
10.7	25.3	7.5	200	A	A	Black	252.98		
10.9	26.7	9.0	200	A	A	Black	163.98		
10.9	25.6	9.0	200	A	A	Black	266.98		
9.1	26.1	7.5	200	A	A	Black	246.98		
9.5	25.5	7.5	200	A	A	Black	263.98		
9.8	26.7	7.5	200	A	A	Black	235.98		
10.9	26.6	9.0	200	A	A	Black	318.98		
10.9	28.7	6.5	100	A	A	Black	324.98	Dodge	
10.9	28.7	6.5	100	A	A	Black	324.98	Dodge	