NEXEN

NEXEN TIRE

AWARD WINNER

reddot

ROADIAN AT Pro RA8

ALL TERRAIN

The Roadian AT Pro has been certified with the Three-Peak Mountain Snowflake (3PMSF), a severe winter certification to withstand heavy snow, ice and tough terrain.

TIRES AVAILABLE TO ORDER	15" – 22" P-METRIC & LT SIZES AVAILABLE	OE FITMENT ON RAM 3500

TREAD WEAR WARRANTY
50,000 MILES (P)
40,000 MILES (LT)

ROAD HAZARD WARRANTY
FIRST 3/32" OR 2 YEARS

ROADSIDE ASSISTANCE
36 MONTHS

FREE TRIAL
45 DAYS OR 500 MILES

NexenTireUSA.com

PATTERN CODE: RA8 (P) METRIC

Product Code	P/LT	Size	XL	LI	SS	PLY	Max Air (psi)	Max Load (lbs)		Rim		Section Width (inch)	Overall Diameter (inch)	Tread Depth (/32")	UTQG			Sidewall	OE
								S	D	Meas.	App.				Tread-wear	Trac.	Temp.		
14392		235/75R15	RF	109	S	4	50	2,271	-	6.5	6.0-8.0	9.3	28.9	13.0	560	A	B	White	
12764		235/70R16		106	S	4	51	2,094	-	7.0	6.0-8.0	9.4	29.0	13.0	560	A	B	White	
14393		245/70R16	RF	111	S	4	50	2,403	-	7.0	6.5-8.0	9.8	29.5	13.0	560	A	B	Black	
12771		245/75R16		111	S	4	51	2,403	-	7.0	6.5-8.0	9.8	30.5	13.0	560	A	B	White	
12760		255/70R16		111	S	4	51	2,403	-	7.5	6.5-8.5	10.2	30.1	13.0	560	A	B	White	
12758		265/70R16		112	S	4	51	2,469	-	8.0	7.0-9.0	10.7	30.6	13.0	560	A	B	White	
12759		265/75R16		116	S	4	51	2,756	-	7.5	7.0-9.0	10.5	31.7	13.0	560	A	B	White	
15211		235/75R17		108	S	4	51	2,205	-	6.5	6.0-8.0	9.3	30.9	13.0	560	A	B	Black	
14436		245/65R17	RF	111	S	4	50	2,403	-	7.0	7.0-8.5	9.8	29.5	13.0	560	A	B	Black	
12784		245/70R17		110	S	4	51	2,337	-	7.0	6.5-8.0	9.8	30.6	13.0	560	A	B	White	
16049	P	255/70R17		110	S	4	51	2,337	-	7.5	6.5-8.5	10.2	31.1	13.0	560	A	B	White	
16060	P	255/75R17		113	S	4	51	2,535	-	7.0	6.5-8.5	10.0	32.0	13.0	560	A	B	White	
12785		265/65R17		112	T	4	51	2,469	-	8.0	7.5-9.5	10.7	30.6	13.0	560	A	B	White	
13637		265/70R17		115	S	4	51	2,679	-	8.0	7.0-9.0	10.7	31.7	13.0	560	A	B	White	
16061	P	285/70R17		117	T	4	51	2,833	-	8.5	7.5-9.5	11.5	32.8	13.0	560	A	B	Black	
15209		255/70R18		113	T	4	51	2,535	-	7.5	6.5-8.5	10.2	32.1	13.0	560	A	B	White	
13123		265/60R18		110	T	4	51	2,337	-	8.0	7.5-9.5	10.7	30.5	13.0	560	A	B	Black	
12780		265/65R18		114	S	4	51	2,601	-	8.0	7.5-9.5	10.7	31.5	13.0	560	A	B	Black	
15210		265/70R18		116	S	4	51	2,756	-	8.0	7.0-9.0	10.7	32.6	13.0	560	A	B	White	
12774		275/65R18		116	T	4	51	2,756	-	8.0	7.5-9.5	11.0	32.1	13.0	560	A	B	Black	
12783		275/55R20	XL	117	T	4	50	2,833	-	8.5	7.5-9.5	11.2	31.9	12.0	560	A	B	Black	
13121		275/60R20		115	S	4	51	2,679	-	8.0	7.5-9.5	11.0	33.0	12.0	560	A	B	Black	
16055		285/45R22	XL	114	H	4	50	2,601	-	9.5	9.0-10.5	11.2	32.1	12.5	560	A	B	Black	
16059		305/45R22	XL	118	T	4	50	2,910	-	10.0	9.5-11.5	11.9	32.8	12.5	560	A	B	Black	

PATTERN CODE: RA8 (LT) METRIC

Product Code	P/LT	Size	XL	LI	SS	PLY	Max Air (psi)	Max Load (lbs)		Rim		Sections Width (inch)	Overall Diameter (inch)	Tread Depth (/32")	UTQG			Sidewall	OE
								S	D	Meas.	App.				Tread-wear	Trac.	Temp.		
12744	LT	235/75R15		104/101	R	6	50	1,985	1,820	6.5	6.0-7.0	9.3	28.9	16.0	-	-	-	White	
13965	LT	215/85R16		115/112	R	10	80	2,680	2,470	6.0	5.5-7.0	8.5	30.4	16.0	-	-	-	White	
12743	LT	225/75R16		115/112	R	10	80	2,680	2,470	6.0	6.0-7.0	8.8	29.3	16.0	-	-	-	Black	
12748	LT	235/85R16		120/116	R	10	80	3,042	2,778	6.5	6.0-7.5	9.3	31.7	16.0	-	-	-	Black	
12740	LT	245/75R16		120/116	R	10	80	3,042	2,778	7.0	6.5-7.5	9.8	30.5	16.0	-	-	-	White	
12738	LT	265/75R16		123/120	R	10	80	3,415	3,085	7.5	7.0-8.0	10.5	31.7	16.0	-	-	-	White	
16278	LT	285/75R16		126/123	R	10	80	3,750	3,415	8.0	7.5-9.0	11.3	32.8	16.0	-	-	-	White	
16286	LT	315/75R16		127/124	R	10	65	3,860	1,600	8.5	8.0-11.0	12.3	34.6	16.0	-	-	-	Black	
13354	LT	235/80R17		120/117	R	10	80	3,085	2,835	6.5	6.0-7.5	9.3	31.8	15.0	-	-	-	White	RAM
13113	LT	245/70R17		119/116	S	10	80	3,000	2,755	7.0	6.5-8.0	9.8	30.6	16.0	-	-	-	White	
12746	LT	245/75R17		121/118	S	10	80	3,195	2,910	7.0	6.5-7.5	9.8	31.5	16.0	-	-	-	Black	
12735	LT	265/70R17		121/118	S	10	80	3,195	2,910	8.0	7.0-8.5	10.7	31.7	16.0	-	-	-	Black	
+ 15218	LT	285/70R17		121/118	S	10	80	3,195	2,910	8.5	7.5-9.0	11.5	32.8	16.0	-	-	-	Black	
+ 16285	LT	285/75R17		121/118	S	10	80	3,195	2,910	8.0	7.5-9.5	11.3	33.9	16.0	-	-	-	Black	
+ 16283	LT	315/70R17		121/118	S	10	65	3,195	2,910	9.5	8.0-11.0	12.7	34.4	16.0	-	-	-	Black	
+ 15217	LT	265/70R18		124/121	S	10	80	3,527	3,197	8.0	7.0-8.5	10.7	32.6	16.0	-	-	-	White	
+ 15215	LT	275/65R18		123/120	S	10	80	3,415	3,085	8.0	7.5-9.0	11.0	32.1	16.0	-	-	-	White	
14760	LT	275/70R18		125/122	R	10	80	3,640	3,305	8.0	7.0-8.5	11.0	33.2	14.0	-	-	-	Black	RAM
+ 15216	LT	285/65R18		125/122	S	10	80	3,640	3,305	8.5	8.0-10.0	11.5	32.6	16.0	-	-	-	Black	
+ 16280	LT	295/70R18		129/126	S	10	80	4,080	3,750	8.5	7.5-10.0	11.8	34.3	16.0	-	-	-	Black	
+ 15214	LT	265/60R20		121/118	S	10	80	3,195	2,910	8.0	7.5-9.5	10.7	32.5	16.0	-	-	-	Black	
+ 16063	LT	275/55R20		120/117	S	10	80	3,085	2,835	8.5	7.5-9.5	11.2	31.9	16.0	-	-	-	Black	
+ 16062	LT	275/60R20		123/120	S	10	80	3,415	3,085	8.0	7.5-9.5	11.0	33.0	16.0	-	-	-	Black	
+ 13111	LT	275/65R20		126/123	S	10	80	3,750	3,415	8.0	7.5-9.5	11.0	34.1	16.0	-	-	-	Black	
+ 15212	LT	285/55R20		122/119	S	10	80	3,305	3,000	9.0	8.0-10.0	11.7	32.4	16.0	-	-	-	Black	
+ 17557	LT	285/60R20		125/122	R	10	80	3,640	3,305	8.5	8.0-10.0	11.5	33.5	16.0				Black	
+ 16279	LT	295/60R20		126/123	S	10	80	3,750	3,415	8.5	8.0-10.0	11.8	33.9	16.0	-	-	-	Black	
+ 15213	LT	305/55R20		121/118	S	10	65	3,195	2,910	9.5	8.5-11.0	12.4	33.2	16.0	-	-	-	Black	
12753	LT	30X9.50R15		104	S	6	50	1,985	-	7.5	6.5-8.5	9.4	29.5	16.0	-	-	-	White	
12750	LT	31X10.50R15		109	S	6	50	2,270	-	8.5	7.0-9.0	10.6	30.5	16.0	-	-	-	White	
+ 16282	LT	33X12.50R15		108	R	6	35	2,205	-	10.0	8.5-11.0	12.5	32.5	16.0	-	-	-	White	
+ 16373	LT	35X12.50R18		128	S	12	80	3,970	-	10.0	8.5-11.0	12.5	34.5	16.0	-	-	-	Black	
+ 16374	LT	35X12.50R20		125	S	12	80	3,640	-	10.0	8.5-11.0	12.5	34.5	16.0	-	-	-	Black	

3 Peak Mountain Snowflake Certified

3PMSF: from DOT 2319 except RAM OEM and Flotation sizes

Technical data can be changed without further notice.

+ Different Sidewall